function OrderController(\$http, \$q, config,

vm.checkCredit = checkCredit;

function checkCredit() {

/ support CORS

var settings = {};

/ object with request data

return \$http.get(settings)

vm.isCreditOk =

// error for a user to see

unction OrderController(creditService) {

vm.checkCredit = checkCredit;

.catch(showError);

function checkCredit() {

vm.isCreditOk;

vm.total = 0;

Assigning controllers

/ Interpret error

.then(function(data)

.catch(function(error) {

/ Add user-identifying info so service gets

/ Use JSONP for this browser if it doesn't

// Unpack JSON data in the response

object to find maxRemainingAmo

vm.total <= maxRemainingAmount</pre>

/ Cope w/ timeout? retry? try alternate

/ service? Re-reject with appropriate

/ the right credit limit for this user.

userInfo) {

var vm = this;

vm.isCreditOk;

vm.total = 0;

POSTER PRODUCED BY MAYFLOWER GMBH

Agile high-performance Teams at Mayflower are well-known for that special kind of software development, that delivers real value for our customers. Backed by more than 460 years of experience at our business locations in Wurzburg

CONTEND RASED ON IOUN ROBER (1) And Munich, Mayflower is a recognized Web & IT service provider in the german-speaking market. Our expertise is driving international projects for customers like Sixt, Vaillant, Media-Saturn, DriveNow or MAN.

CONTEND RASED ON IOUN ROBER (2) And Munich, Mayflower is a recognized Web & IT service provider in the german-speaking market. Our expertise is driving international projects for customers like Sixt, Vaillant, Media-Saturn, DriveNow or MAN. Agile high-performance Teams at Mayflower are well-known for that special and Munich, Mayflower is a recognized Web & IT service provider in the mail kontakt@mayflower.de

Mannhardtstr. 6

80538 München

templateUrl:

tel +49 89 242054 1177

OFFICE WURZBURG Gneisenaustr. 10/11

tel +49 931 35965 1177

97074 Würzburg

M YFLOWER

## controllerAs view syntax

Why? Controllers are constructed, "newed" up, and provide a single new instance, and the controllerAs syntax is closer to that of a JavaScript constructor than he classic \$scope syntax.

Why? It promotes the use of binding to a "dotted" object in the View e.g. customer.name instead of name), which is more contextual, easier to read, and avoids any reference issues that may occur without "dotting".

iv ng-controller="CustomerController">

Why? Helps avoid using \$parent calls in Views with nested controllers.

{{ name }}

## {{ customer.name }}

Use the controllerAs syntax over the classic controller with \$scope syntax. The controllerAs syntax uses this inside controllers which gets bound to \$scope.

function CustomerController(\$scope) { \$scope.sendMessage = function() { };

\* recommended - but see next section \*/ unction CustomerController() { this.name = {}; this.sendMessage = function() { };

sistent variable name such as vm, which stands for ViewModel. ing this problem.

\* avoid \*/ unction CustomerController() { this.name = {};

\* recommended \*/ unction CustomerController() { var vm = this;  $vm.name = {};$ vm.sendMessage = function() { };

lote: You can avoid any jshint warnings by placing the comment above the line f code. However it is not needed when the function is named using UpperCasg, as this convention means it is a constructor function, which is what a controller in Angular.

Single responsibility

service. Note: All Angular services are singletons.

Accessible members up top

tested (and/or mocked).

\* avoid \*/

return {

to scroll to see what is exposed.

nction dataService() {

var someValue = '';

function validate() {

save: save,

someValue: someValue,

validate: validate

function save() {

nique derived from the Revealing Module Pattern.

Note: When creating watches in a controller using controller as, you can watch he vm.\* member using the following syntax. (Create watches with caution as they add more load to the digest cycle.)

\$log.info('vm.title was %s', original);

actories should have a single responsibility, that is encapsulated by its context.

-actories are singletons and return an object that contains the members of the

Expose the callable members of the service (its interface) at the top, using a tech-

Why? Placing the callable members at the top makes it easy to read and helps

you instantly identify which members of the service can be called and must be unit

Why? This is especially helpful when the file gets longer as it helps avoid the need

Why? Setting functions as you go can be easy, but when those functions are more

than 1 line of code they can reduce the readability and cause more scrolling.

Defining the callable interface via the returned service moves the implementation

details down, keeps the callable interface up top, and makes it easier to read.

Once a factory begins to exceed that singular purpose, a new factory should be

\$log.info('vm.title is now %s', current);

input ng-model="vm.title"/> anction SomeController(\$scope, \$log) { var vm = this; vm.title = 'Some Title'; \$scope.\$watch('vm.title', function(current, original) {

### Bindable members up top

Place bindable members at the top of the controller, alphabetized, and not spread Jse the controllerAs syntax over the classic controller with \$scope syntax. Why? Placing bindable members at the top makes it easy to read and helps you instantly identify which members of the controller can be bound and used in the

> Why? Setting anonymous functions in-line can be easy, but when those functions are more than 1 line of code they can reduce the readability. Defining the functions below the bindable members (the functions will be hoisted) moves the implementation details down, keeps the bindable members up top, and makes it easier to

> > vm.gotoSession = function() {

vm.refresh = function() {

vm.search = function() {

vm.sessions = [];

var vm = this;

recommended \*/

vm.title = 'Sessions';

unction SessionsController() {

vm.refresh = refresh;

vm.title = 'Sessions';

function gotoSession() {

function refresh() {

function search() {

var vm = this;

\* lines

\* code

\* affects

vm.search = search;

vm.title = 'Sessions';

vm.title = 'Sessions';

vm.sessions = [];

unction SessionsController(data) {

vm.gotoSession = gotoSession;

vm.refresh = function() {

ability is not affected.

/\* avoid \*/

vm.search = search;

vm.sessions = [];

vm.gotoSession = gotoSession;

function SessionsController() { var vm = this;

div ng-controller= "CustomerController as customer">

## controllerAs controller syntax

Why? controllerAs is syntactic sugar over \$scope. You can still bind to the View and still access \$scope methods.

Why? Helps avoid the temptation of using \$scope methods inside a controller when it may otherwise be better to avoid them or move the method to a factory, and reference them from the controller. Consider using \$scope in a controller only when needed. For example when publishing and subscribing events using \$emit, \$broadcast, or \$on consider moving these uses to a factory and invoke from the

### controllerAs with vm

Jse a capture variable for this when using the controllerAs syntax. Choose a con-Why? The this keyword is contextual and when used within a function inside a controller may change its context. Capturing the context of this avoids encounter-

this.sendMessage = function() { };

\* recommended \*/ unction SessionsController(sessionDataService) { var vm = this;

vm.gotoSession = gotoSession; / 1 liner is OK vm.refresh = sessionDataService.refresh; vm.search = search; vm.sessions = [];

## Function declarations

to hide implementation details Use function declarations to hide implementation details. Keep your bindable members up top. When you need to bind a function in a controller, point it to a function declaration that appears later in the file. This is tied directly to the section Bindable members up top. For more details see this post.

Why? Placing bindable members at the top makes it easy to read and helps you instantly identify which members of the controller can be bound and used in the View. (Same as above.)

Why? Placing the implementation details of a function later in the file moves that complexity out of view so you can see the important stuff up top. Why? Function declaration are hoisted so there are no concerns over using a func-

This way bindings are mirrored across the host object, primitive values cannot

Use function declarations to hide implementation details. Keep your accessible

members of the factory up top. Point those to function declarations that appears

Why? Placing accessible members at the top makes it easy to read and helps you

Why? Placing the implementation details of a function later in the file moves that

Why? Function declaration are hoisted so there are no concerns over using a func-

Why? You never have to worry with function declarations that moving var a before

instantly identify which functions of the factory you can access externally.

complexity out of view so you can see the important stuff up top.

var b will break your code because a depends on b.

Why? Order is critical with function expressions

tion before it is defined (as there would be with function expressions).

tion before it is defined (as there would be with function expressions).

function dataService() {

save: save,

someValue: someValue,

validate: validate

var service = {

return service;

function save() {

/\* \*/

Function declarations

later in the file.

function validate() {

update alone using the revealing module pattern.

o hide implementation details

Why? You never have to worry with function declarations that moving var a before var b will break your code because a depends on b.

> Why? Order is critical with function expressions \* avoid using function expressions. \*/ unction AvengersController(avengersService, logger) { var vm = this; vm.avengers = []; vm.title = 'Avengers';

var activate = function() { return getAvengers().then(function() { logger.info('Activated Avengers View');

var getAvengers = function() { return avengersService.getAvengers() .then(function(data) vm.avengers = data; return vm.avengers;

vm.getAvengers = getAvengers;

activate();

Notice that the important stuff is scattered in the preceding example. In the example below, notice that the important stuff is up top. For example, the members bound to the controller such as vm.avengers and vm.title. The implementation details are down below. This is just easier to read.

\* recommended: \* Using function declarations \* and bindable members up top. unction AvengersController(avengersService, logger) { var vm = this; vm.avengers = []; vm.getAvengers = getAvengers; vm.title = 'Avengers';

activate(); function activate() { return getAvengers().then(function() { logger.info('Activated Avengers Note: If the function is a 1 liner consider keeping it right up top, as long as read-

function getAvengers() { return avengersService.getAvengers() .then(function(data) { vm.avengers = data; return vm.avengers;

### Keep controllers focused

Define a controller for a view, and try not to reuse the controller for other views. Instead, move reusable logic to factories and keep the controller simple and fo-

Why? Reusing controllers with several views is brittle and good end-to-end (e2e) function config (\$routeProvider) { test coverage is required to ensure stability across large applications.

## Defer controller logic to services

Defer logic in a controller by delegating to services and factories. Why? Logic may be reused by multiple controllers when placed within a service and exposed via a function.

Why? Logic in a service can more easily be isolated in a unit test, while the calling logic in the controller can be easily mocked. Why? Removes dependencies and hides implementation details from the con-

Why? Keeps the controller slim, trim, and focused.

\* avoid using function expressions \*/

var getAvengers = function() {

var getAvengerCount = function() {

var getAvengersCast = function() {

var prime = function() {

var service = {

return service;

ready: ready

var isPrimed = false;

var primePromise;

function dataservice (\$http, \$location, \$q,

// implementation details go here

getAvengersCast: getAvengersCast,

getAvengerCount: getAvengerCount,

getAvengers: getAvengers,

var ready = function(nextPromises) {

Please visit github.com/johnpapa/angular-styleguide for more information on the original source.

Limit 1 per file

Create one directive per file. Name the file for the directive.

/ Get the credit service base URL from when the directive is removed" ... from the Angular documentation. // Set credit service required headers // Prepare URL query string or data

directives.js \*/

.module('app.widgets') /\* order directive that is specific to .directive('orderCalendarRange',

/\* sales directive that can be used anywhere across the sales app \*/ .directive('salesCustomerInfo',

/\* spinner directive that can be used anywhere across apps \* .directive('sharedSpinner', sharedSpinner);

/\* implementation details \*, inction salesCustomerInfo() { /\* implementation details \*

inction sharedSpinner() { return creditService.isOrderTotalOk(vm.total) .then(function(isOk) { vm.isCreditOk = isOk;

When a controller must be paired with a view and either component may be reused by other controllers or views, define controllers along with their routes. Note: If a view is loaded via another means besides a route, then use the ng-con-

troller="Avengers as vm" syntax. Why? Pairing the controller in the route allows different routes to invoke different pairs of controllers and views. When controllers are assigned in the view using ng-controller, that view is always associated with the same controller.

\* when using with a route \* and dynamic pairing is desired

route-config.js angular .module('app') .config(config);

\$routeProvider .when('/avengers', templateUrl: 'avengers.html'

- avengers.html --> <div ng-controller="AvengersController as vm">

</div> route-config.js .module('app') .config(config);

nction config(\$routeProvider) { \$routeProvider .when('/avengers', { templateUrl: 'avengers.html', controller: 'Avengers', controllerAs: 'vm'

-- avengers.html -->

## Manipulate DOM in a directive

Why? It is easy to mash all the directives in one file, but difficult to then break those out so some are shared across apps, some across modules, some just for one

Why? One directive per file is easy to maintain. Note: "Best Practice: Directives should clean up after themselves. You can use element.on('\$destroy', ...) or scope.\$on('\$destroy', ...) to run a clean-up function

the order module \*/ orderCalendarRange)

salesCustomerInfo)

nction orderCalendarRange() {

calendarRange.directive.js \*/

.module('sales.order')

/\* implementation details \*/ /\* recommended \*/

@desc order directive that is specific to the order module at a company named Acme @example <div acme-order-calendar-range></div>

.directive('acmeOrderCalendarRange', orderCalendarRange); inction orderCalendarRange() { /\* implementation details \*

recommended \*/ customerInfo.directive.js \*/

\* **@desc** sales directive that can be used anywhere cross the sales app at a company named Acme @example <div acme-sales-customer-info></div

angular .module('sales.widgets') .directive('acmeSalesCustomerInfo', salesCustomerInfo);

function salesCustomerInfo() { /\* implementation details \*/ '\* recommended \*

\* spinner.directive.js \*/ anywhere across apps at a company named Acme

angular .module('shared.widgets') .directive('acmeSharedSpinner',

sharedSpinner); function sharedSpinner() { /\* implementation details \*/

Note: There are many naming options for directives, especially since they can be used in narrow or wide scopes. Choose one that makes the directive and its file name distinct and clear. Some examples are below, but see the Naming section for more recommendations.

Note: You can use a provider such as the routerHelperProvider shown below to

routerHelper.configureStates(getStates());

When manipulating the DOM directly, use a directive. If alternative ways can be used such as using CSS to set styles or the animation services, Angular templating ngShow or ngHide, then use those instead. For example, if the directive simply hides and shows, use ngHide/ngShow.

Why? DOM manipulation can be difficult to test, debug, and there are often better ways (e.g. CSS, animations, templates)

### Provide a unique directive prefix

Provide a short, unique and descriptive directive prefix such as acmeSalesCustomerInfo which would be declared in HTML as acme-sales-customer-info. Why? The unique short prefix identifies the directive's context and origin. For example a prefix of cc- may indicate that the directive is part of a CodeCamper app

Note: Avoid ng- as these are reserved for Angular directives. Research widely used directives to avoid naming conflicts, such as ion- for the Ionic Framework.

### Restrict to elements and attributes

while acme- may indicate a directive for the Acme company.

When creating a directive that makes sense as a stand-alone element, allow restrict E (custom element) and optionally restrict A (custom attribute). Generally, if it could be its own control, E is appropriate. General guideline is allow EA but lean towards implementing as an element when it's stand-alone and as an attribute when it enhances its existing DOM element.

Why? It makes sense. Why? While we can allow the directive to be used as a class, if the directive is truly acting as an element it makes more sense as an element or at least as an attribute.

Note: EA is the default for Angular 1.3 + <div class="my-calendar-range"></div>

/\* avoid \*/

.module('app.widgets') .directive('myCalendarRange', myCalendarRange); function myCalendarRange() {

var directive = { link: link, templateUrl: '/template/is/located/here.html', restrict: 'C' return directive;

<!-- recommended -->

<my-calendar-range></my-calendar-range> <div my-calendar-range></div> /\* recommended \*/ .module('app.widgets') .directive('myCalendarRange', myCalendarRange);

function link(scope, element, attrs) {

unction myCalendarRange() { var directive = { link: link, templateUrl: '/template/is/located/here.html' restrict: 'EA'

## Directives and controllerAs

return directive;

Use controllerAs syntax with a directive to be consistent with using controllerAs with view and controller pairings. Why? It makes sense and it's not difficult.

function link(scope, element, attrs) {

Note: The directive below demonstrates some of the ways you can use scope inside of link and directive controllers, using controllerAs.

## Note: Regarding dependency injection, see Manually identify dependencies. Note: The directive's controller is outside the directive's closure. This style eliminate

Define 1 component per file. <div my-example max="77"></div> controller, and defines a factory all in the same file.

.module('app') .directive('myExample', myExample); angular ction myExample() { var directive = { restrict: 'EA',

'app/feature/example.directive.html', scope: { max: '=' link: linkFunc,

controller: ExampleController, controllerAs: 'vm', bindToController: true // because the scope is isolated

return directive; function linkFunc(scope, el, attr, ctrl) { console.log('LINK: scope.min = %s \*\*\* should be undefined', scope.min); console.log('LINK: scope.max = %s \*\*\* should be undefined', scope.max); console.log('LINK: scope.vm.min = %s', scope.vm.min); console.log('LINK: scope.vm.max = %s',

scope.vm.max);

ExampleController.\$inject = ['\$scope']; anction ExampleController(\$scope) { // Injecting \$scope just for comparison var vm = this;

vm.min = 3;console.log('CTRL: \$scope.vm.min = %s', \$scope.vm.min); console.log('CTRL: \$scope.vm.max = %s', console.log('CTRL: vm.min = %s', vm.min); console.log('CTRL: vm.max = %s', vm.max);

!-- example.directive.html --> <div>hello world</div> <div>max={{vm.max}}<input ng-model="vm.max"/> <div>min={{vm.min}}<input ng-model="vm.min"/>

Note: You can also name the controller when you inject it into the link function and access directive attributes as properties of the controller.

// Alternative to above example function linkFunc(scope, el, attr, vm) { console.log('LINK: scope.min = %s \*\*\* should be undefined', scope.min); console.log('LINK: scope.max = %s \*\*\* should be undefined', scope.max); console.log('LINK: vm.min = %s', vm.min); console.log('LINK: vm.max = %s', vm.max);

Use bindToController = true when using controllerAs syntax with a directive when you want to bind the outer scope to the directive's controller's scope.

Why? It makes it easy to bind outer scope to the directive's controller scope. Note: bindToController was introduced in Angular 1.3.0. <div my-example max="77"></div>

angular .module('app') .directive('myExample', myExample); function myExample() { var directive = { restrict: 'EA', templateUrl: 'app/feature/example.directive.html', scope: { max: '='

controller: ExampleController, controllerAs: 'vm', bindToController: true return directive;

unction ExampleController() { console.log('CTRL: vm.min = %s', vm.min); console.log('CTRL: vm.max = %s', vm.max);

div>max={{vm.max}}<input ng-model="vm.max"/>

<div>min={{vm.min}}<input ng-model="vm.min"/>

iv>hello world</div>

# issues where the injection gets created as unreachable code after a return.

The following example defines the app module and its dependencies, defines a /\* avoid \*/

.module('app', ['ngRoute']) .controller('SomeController', SomeController) .factory('someFactory', someFactory);

function someFactory() { } The same components are now separated into their own files.

function SomeController() { }

/\* recommended \*/ // app.module.js angular .module('app', ['ngRoute']); \* recommended \*/

someController.js angular .module('app') .controller('SomeController', SomeController);

unction SomeController() { } \* recommended \*/ / someFactory.js angular .module('app')

.factory('someFactory', someFactory);

## Need support for your AngularJS demands?

function someFactory() { }

AngularJS Development We provide first class agile development based on Angular and Node.js.

AngularJS Training Dur training combines the knowledge of our well known conference speakers with real life knowhow from man years of practical angular development. W go beyond full frontal talks and offer coding dojos, pair programming and codreviews with the team to train your team hands on using your own project. Why? Separating feature areas into modules makes it easier to test the modules

AngularJS Consulting We provide fast hands-on problem solution for your Angular development. Performance, quality, security – ask us. mayflower.de

# Services

ingletons Services are instantiated with the new keyword, use this for public methods and variables. Since these are so similar to factories, use a factory instead for consis-

Note: All Angular services are singletons. This means that there is only one instance of a given service per injector. // service angular .module('app') .service('logger', logger);

unction logger() { this.logError = function(msg) { / factory

angular .module('app') .factory('logger', logger); unction logger() { logError: function(msg) {

plication root module whose role is to tie your other modules together provides a

views, or other logic not related to pulling the app together muddies the app

Why? The app module becomes a manifest that describes which modules help

module and make both sets of features harder to reuse or turn off.

very straightforward way to add or remove modules from your application.

tures in their own modules.

define the application.

of the sprint or iteration.

in isolation and reuse code.

eused across applications.

any shared or reusable modules.

cation's features.

outside of this application.

Controller name suffix

monly used and more explicitly descriptive.

troller);

and reference factories.

/\* recommended \*/

Reusable blocks are modules

The application root module depends on the app specific feature modules and

Why? The main app module contains a quickly identifiable manifest of the appli-

Why? Intra-App features such as shared data services become easy to locate

Note: This is a strategy for consistency. There are many good options here.

Choose one that is consistent, follows Angular's dependency rules, and is easy

and share from within app.core (choose your favorite name for this module).

pulled in as a dependency in other applications and still work.

l teature areas are modules

Many small, self contained modules

nis means we can plug in new features as we develop them.

Create small modules that encapsulate one responsibility. Use unique naming conventions with separators for sub-modules. Why? Modular applications make it easy to plug and go as they allow the devel-Why? Unique names help avoid module name collisions. Separators help deopment teams to build vertical slices of the applications and roll out incrementally. fine modules and their submodule hierarchy. For example app may be your root

### Definitions (aka setters) Create an app module

Create an application root module whose role is pull together all of the module Declare modules without a variable using the setter syntax. With 1 component per file, there is rarely a need to introduce a variable for the module. and features of your application. Name this for your application. Why? Angular encourages modularity and separation patterns. Creating an ap-

## Keep the app module thin

/\* recommended \*/ Only put logic for pulling together the app in the application module. Leave fea-.module('app', [ 'ngAnimate', 'ngRoute', Why? Adding additional roles to the application root to get remote data, display

### 'app.shared', 'app.dashboard'

'ngAnimate',

'app.shared',

'app.dashboard'

Instead use the simple setter syntax.

'ngRoute',

Avoid naming collisions

dependencies of app.

module while app.dashboard and app.users may be modules that are used as

Getters When using a module, avoid using a variable and instead use chaining with the

getter syntax. This produces more readable code and avoids variable collisions

app = angular.module('app', [

Create modules that represent feature areas, such as layout, reusable and shared r app = angular.module('app'); services, dashboards, and app specific features (e.g. customers, admin, sales). app.controller('SomeController', SomeController); Why? Self contained modules can be added to the application with little or no

inction SomeController() { } Why? Sprints or iterations can focus on feature areas and turn them on at the end /\* recommended \*/ angular .module('app')

.controller('SomeController',

function SomeController() { }

once, then retrieved from that point and after. uch as exception handling, logging, diagnostics, security, and local data stash-/\* recommended \*/ / to set a module Vhy? These types of features are needed in many applications, so by keeping

hem separated in their own modules they can be application generic and be angular.module('app', []);

### / to get a module angular.module('app');

Named vs. anonymous functions Use named functions instead of passing an anonymous function in as a callback.

### Why? This produces more readable code, is much easier to debug, and reduces the amount of nested callback code. Why? Each feature area contains a manifest of what it depends on, so it can be

.controller('DashboardController', function() { .factory('logger', function() { });

Our structures vary slightly between projects but they all follow these guidelines .controller('DashboardController', for structure and modularity. The implementation may vary depending on the fea-DashboardController); tures and the team. In other words, don't get hung up on an exact like-for-like

structure but do justify your structure using consistency, maintainability, and effi-In a small app, you can also consider putting all the shared dependencies in the angular app module where the feature modules have no direct dependencies. This makes .factory('logger', logger); it easier to maintain the smaller application, but makes it harder to reuse modules

Directive component names

function logger() { }

Append the controller name with the suffix Controller. This behaviour is more comdescribe the area that the directives belong (some example are company prefix

or project prefix). This provides a consistent way to quickly identify and reference

/ avenger-profile.directive.is angular .module .directive('xxAvengerProfile',

/\* recommended \*/

xxAvengerProfile); usage is <xx-avenger-profile> </xx-avenger-profile>

unction xxAvengerProfile() { }

## Modules

When there are multiple modules, the main module file is named app.module.is while other dependent modules are named after what they represent. Example: an admin module is named admin.module.js. The respective registered module names would be app and admin. This provides consistency for multiple module apps, and for expanding to large applications. And it's an easy way to use task automation to load all module definitions first, then all other angular files (for bundling).

## Contiguration

A configuration file for the main app module is named app.config.js (or simply config.js). A configuration for a module named admin.module.js is named admin. config.is. This separates configuration from module definition, components, and active code and provides an identifiable place to set configuration for a module.

the main module and admin.route.js for the admin module. Even in smaller apps we prefer this separation from the rest of the configuration.

Use the AngularUI router for client-side routing.

help configure states across files, during the run phase.

.module('app.customers')

unction appRun(routerHelper) {

.module('blocks.router')

routerHelperProvider);

.provider('routerHelper',

aterHelperProvider.\$inject =

['\$locationProvider', '\$stateProvider',

'\$urlRouterProvider'];

.run(appRun);

@ngInject \*/

ones including nested routes and states.

\* recommended \* Using function declarations \* and accessible members up top. function dataservice(\$http, \$location, \$q,

exception, logger) {

var service = { getAvengersCast: getAvengersCast, getAvengerCount: getAvengerCount, getAvengers: getAvengers, ready: ready

var isPrimed = false;

var primePromise;

return service;

function prime() {

function getAvengers() { // implementation details go here function getAvengerCount() { // implementation details go here

function getStates() { return [ state: 'customer', config: { abstract: true, function getAvengersCast() { template: '<ui-view // implementation details go here class="shuffle-animation"/>', url: '/customer' // implementation details go here function ready(nextPromises) { routerHelperProvider.js // implementation details go here

angular

Client-side routing is important for creating a navigation flow between views and function routerHelperProvider(\$locationProvider, composing views that are made of many smaller templates and directives. /\* jshint validthis:true \*/ this.\$get = RouterHelper; Why? UI router offers all the features of the Angular router plus a few additional \$locationProvider.html5Mode(true); RouterHelper.\$inject = ['\$state']; Why? The syntax is quite similar to the Angular router and is easy to migrate to /\* @ngInject \*/

function RouterHelper(\$state) {

var service = {

var hasOtherwise = false;

getStates: getStates return service; function configureStates(states, otherwisePath) states.forEach(function(state) { \$stateProvider.state(state.state, state.config); if (otherwisePath && !hasOtherwise) hasOtherwise = true; \$urlRouterProvider.otherwise( otherwisePath);

configureStates: configureStates,

return \$state.get(); Define routes for views in the module where they exist. Each module should con tain the routes for the views in the module. Why? Each module should be able to stand on its own.

Why? When removing a module or adding a module, the app will only contain

Why? This makes it easy to enable or disable portions of an application without

function getStates() {

routes that point to existing views.

concern over orphaned routes.

## Naming guidelines

are 2 names for most assets:

Use consistent names for all components following a pattern that describes the component's feature then its type. Our preferred pattern is feature.type.is. There

 The file name (avengers.controller.js) The registered component name with Angular (AvengersController) Why? Naming conventions help provide a consistent way to find content at a glance. Consistency within the project is vital. Consistency with a team is important. Consistency across a company provides tremendous efficiency.

Why? The naming conventions should simply help you find your code faster and

Feature tile names

make it easier to understand.

/\* recommended \*/

/ controllers

Use consistent names for all components following a pattern that describes the component's feature then its type. Our recommended pattern is feature.type.js. Why? Provides a consistent way to quickly identify components. Thus provides pattern matching for any automated tasks.

avengers.controller.spec.js / services/factories logger.service.js logger.service.spec.js / constants

avengers.controller.js

avengers.routes.js avengers.routes.spec.js

avengers.config.js

/ module definition

avengers.module.js

constants.js

avenger-profile.directive.js

Controllers

avengers.spec.js

karma or other test runners.

avengers.js

Note: Another common convention is naming controller files without the word controller in the file name such as avengers.js instead of avengers.controller.js. All other conventions still hold using a suffix of the type. Controllers are the most common type of component so this just saves typing and is still easily identifiable. \* recommended \*/

## Test file names Name test specifications similar to the component they test with a suffix of spec.

/\* recommended \*/ avengers.controller.spec.js logger.service.spec.js avengers.routes.spec.js

This will help to quickly identify components and provides pattern matching for

### Controller names Use consistent names for all controllers named after their feature. Use Upper-CamelCase for controllers, as they are constructors.

avenger-profile.directive.spec.js

Why? UpperCamelCase is conventional for identifying object that can be instantiated using a constructor. /\* recommended \*/ / avengers.controller.js angular

.controller('HeroAvengersController',

function HeroAvengersController() { }

HeroAvengersController);

Why? Provides a consistent way to quickly identify and reference controllers.

.module

### /\* recommended \*/ / avengers.controller.js angular .module .controller('AvengersController', AvengersCon-

function AvengersController() { }

factory and service names Use consistent names for all factories and services named after their feature. Use camel-casing for services and factories. Avoid prefixing factories and services

with \$. Only suffix service and factories with Service when it is not clear what they

are (i.e. when they are nouns). This provides a consistent way to quickly identify

### Why? Avoids name collisions with built-in factories and services that use the \$ Why? Clear service names such as logger do not require a suffix.

/ logger.service.js angular .module .factory('logger', logger); function logger() { }

.service('customerService', customerService);

### \* recommended \*/ / credit.service.js .module .factory('creditService', creditService);

function customerService() { }

.module

unction creditService() { } / customer.service.js angular

Separate route configuration into its own file. Examples might be app.route.js for

Separate configuration for a module into its own file named after the module.

## Setting vs. getting Only set once and get for all other instances. A module should only be created reate modules that represent reusable application blocks for common services

SomeController);